



Schematic



NO.	ECN NO.	DESCRIPTION	REV.	DRAW	DATE
1					
2					
3					

PARAMETER	SPECIFICATIONS
OPERATING TEMPERATURE	0°C To +70°C
STORAGE TEMPERATURE	-25°C To +125°C
TURNS RATIO	1:1±5%
OPEN CIRCUIT INDUCTANCE(OCL)	350uH MIN@100KHz/100mV With 8mA DC Bias For (CHANNEL 1,2,3,4)
INSERTION LOSS(IL)	-1.0dB MAX@1MHz-100MHz;
RETURN LOSS(RL) (Z out=100 OHM)	-18dB MIN@1MHz-30MHz; -14dB MIN@30-60MHz; -12dB MIN@60-80MHz; -10dB MIN@80MHz-100MHz;
CROSSTALK (ADJACENT CHANNELS)	-30dB MIN@1-100MHz;
(DCMR)	-40dB MIN@30MHz; -35dB MIN@60MHz; -30dB MIN@100MHz;
HI-POT	1500Vrms
STANDARD	Designed to meet IEEE802.3ab Requirement

Mechanical



产品客户图 Customer Drw		深圳市毅远达电子有限公司			
未注公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	0.XX	±0.10	Description	1000 BASE-T Ethernet Isolation Transformer 24PIN SMD PROFILE PACKAGE	
	X.XX	±0.25			
	XX.XX	±0.25	比例 SCALE	2021.12.16	品名 TITLE
	X°	±2°		1/1	S24508
张数 SHEET	1/1	角法 PROJ.	设计 DESIGN	2021.12.16	料号 ITEM NO.
单位 UNIT	mm	大小 SIZE	A4	2021.12.16	图号 DWG NO.
		版本 REV.	A0	核准 APPROVED	